

List of figures

Figure 1-1 Basic setup of proposed Architecture	17
Figure 1-2 Location Fingerprinting	17
Figure 4-1 Trilateration Algorithm	34
Figure 4-2 Location Fingerprinting Algorithm.....	35
Figure 4-3 Anchor Node (AN1).....	37
Figure 4-4 Visitor Node (MN1) & Pursuit Node (RS1)	38
Figure 4-5 Hardware Node	38
Figure 4-6 Node placement in OSA location.....	40
Figure 4-7 First OSA location.....	40
Figure 4-8 Second OSA location	41
Figure 4-9 CIB location 1	42
Figure 4-10 CIB location 2	42
Figure 4-11 Experimental test bench with deployed WSN for outdoor location .	44
Figure 4-12 Real Experimental test bench with deployed WSN for outdoor location.....	45
Figure 4-13 Real plot of Omnidirectional behavior in specific Outdoor location	47
Figure 4-14 Flowchart for Unilateral Algorithm	48
Figure 4-15 Approach towards Anchor Node- VPM Protocol based.....	49
Figure 4-16 Training pattern in -X, X, -Y, Y direction using VPM Protocol	50
Figure 5-1 System Architecture	57
Figure 5-2 Outdoor location.....	57
Figure 6-1 Detailed hardware/Control Architecture of Mobile Sensor Node (RescOp)	67
Figure 6-2 Mobile Sensor Node.....	68
Figure 6-3 Frame Type	69
Figure 7-1 Battery Performance.....	77
Figure 7-2 RSSI (dBm) Complex Indoor Building (CIB)	78
Figure 7-3 Throughput RescOp Node with 100 Packets	79
Figure 7-4 Throughput RescOp Node with 500 Packets	79

Figure 7-5 RSSI (dBm) in OSA.....	80
Figure 7-6Throughput unidirectional of RescOp Node.....	80
Figure 7-7Throughput bidirectional of RescOp Node.....	81
Figure 7-8Q-Q Plot for CIB RSSI.....	82
Figure 7-9Q-Q Plot for CIB throughput (100 Packets).....	83
Figure 7-10Q-Q Plot for CIB throughput (500 Packets).....	83
Figure 7-11Q-Q Plot for OSA RSSI.....	84
Figure 7-12Q-Q Plot for OSA throughput (100 Packets).....	84
Figure 7-13Q-Q Plot for OSA throughput (500 Packets).....	85
Figure 7-14 Path as Computed by Hybrid TLBO -Unilateral Algorithm for Outdoor Location.....	87
Figure 7-15 Path as Computed by Hybrid TLBO-Unilateral Algorithm for Indoor Location.....	88
Figure 7-16 Path as Computed by Hybrid TLBO-Unilateral Algorithm for Dense Forest Outdoor Location.....	89
Figure 7-17 Measured data in Outdoor Location.....	92
Figure 7-18 Plot for Outdoor Location for Normality.....	93
Figure 7-19 Plot for throughput of Outdoor Location for Normality Check – using LNSM.....	93
Figure 7-20 Plot for Outdoor Location for Normality Check -Hybrid TLBO Unilateral Algorithm.....	95
Figure 7-21 Plot for throughput of Outdoor Location for Normality Check - Hybrid TLBO Unilateral Algorithm.....	95
Figure 7-22RSSI (dBm) Complex Indoor Building (CIB).....	98
Figure 7-23RSSI (dBm) OSA.....	99
Figure 7-24 RF signature capturing by AN1 location 1 (vehicle carrying MN1 moves toward AN1).....	100
Figure 7-25 RF signature capturing by AN1 location 1 (vehicle carrying MN1 moves away from AN1).....	100

Figure 7-26 RF signature capturing by AN1 location 2 (vehicle carrying MN1 moves away from AN1).....	101
Figure 7-27 RF signature capturing by AN1 location 3 (vehicle carrying MN1 moves away from AN1).....	101
Figure 7-28 RF signature capturing by AN1 location 4 (vehicle carrying MN1 moves away from AN1).....	102
Figure 7-29 Handshaking of MN1 from AN1 location 1 to AN1 location 2.....	102
Figure 7-30 RF signature capturing by AN1 location 6 (vehicle speed is 48 km/h).....	103
Figure 7-31 RF signature capturing by AN1 location 8 (vehicle speed is 25 km/h).....	103
Figure 7-32 Handshaking of MN1 from AN1 location 7 to AN1 location 8 (vehicle speed is 46 km/h)	104
Figure 7-33 Handshaking of MN1 from AN1 location 3 to AN1 location 4 (vehicle speed is 34 km/h)	104